



SPECIAL SELF-FLUXING ALUMINUM BRAZING ALLOY

MALLOY makes maintenance

EASIER, FASTER and MORE RELIABLE

to significantly

LOWER COSTS
SAVE PARTS and
REDUCE DOWNTIME

- Easy applications even on thin surfaces.
- User-friendly thanks to the flux incorporated in the rod.
- Same color of Aluminum.
- Flows freely yielding very strong joints.



SPECIAL ADVANTAGES

Malloy 57 - Special self-fluxing Aluminum Brazing Alloy has been developed to allow everyone the Aluminum brazing successfully.

- Easy applications even on thin surfaces with a simple PROPANE TORCH.
- Doesn't require added flux as the right quantity is integrated in the rod.
- Melts 100°C below the melt point of Aluminum, eliminating so any risk of destroying the base metal.
- Braze all Aluminum Alloys (excluded 2000 and 5000 series).

SUPERIOR PROPERTIES

- High mechanical strength (180 N/mm²).
- Good corrosion resistance.
- Non corrosive flux type— no need to remove the residual flux after brazing.
- Same color of aluminum.
- Smooth and porosities-free deposits.

APPLICATIONS

Malloy 57 offers all its benefits in all the following cases:

 Radiators repairing • Air Conditioning repairs • Evaporator coils • Car body shop • Aluminum casting repairs • Frames • Gearbox cases • Porosities filling • Pipes • And many others...

For information about MALLOY products applications, or solutions for your specific problems, don't hesitate to contact us via web: www.malloy.it, or e-mail: info@malloy.it, or your local distributor.

We will be glad to do our best in assisting you.

